

# SF-VIK002-S-WIP

Video-intercom kit

Tecnología IP & WiFi

Includes panel and monitor

MF Reader | PoE Standard

Mobile App with P2P

Surface mounting



Safire

Intercom Kit

IP Interface

Kit consisting of: SF-VI111-IPW-1MF external video intercom panel for surface

2Mpx HD camera board

SF-VIDISP01-7WIP 7" LCD TFT interior monitor

Powered by Standard PoE (IEEE 802.3af)

Monitoring through Safire Control Center-software or mobile app

# Specifications

|                      |  |
|----------------------|--|
| <b>Panel</b>         |  |
| Brand                | Safire   |
| Model                | SF-VI111-IPW-1MF   |
| Operating system     | LINUX OS   |
| Image sensor         | 1/3" 2 Megapixel CMOS  |
| Audio                | Bidirectional audio with microphone and speaker                |
| Access Control       | Door opening with MF card 13.65MHz to 256                      |
| Keypad               | Mechanical button with LED backlit name-tag                    |
| Relay                | 1 for lock control.  |
| Inputs               | Exit button, feedback, door sensor, tamper                     |
| Remote access        | Web browser, phone app or Safire Control Center-software       |
| Network interface    | Ethernet 10/100 BaseT, WiFi                                    |
| Power                | DC 12 V / 1000 mA max. / IEEE802.3af PoE                       |
| Degree of protection | IP65   |
| Material             | Plastic  |
| Temp. operation      | -40° C ~ +53° C  |
| Dimensions           | 138 (H) x 65 (W) x 27 (D) mm                                   |
| Weight               | 400 g  |
| <b>Monitor</b>       |  |
| Brand                | Safire   |
| Model                | SF-VIDISP01-7WIP   |
| LCD                  | 7" 1024x600, Capacitive  |
| Operation mode       | Tactile Buttons  |
| Inputs               | 8 Configurable alarm entries                                   |
| Audio                | Two-way audio with microphone and speaker with noise reduction |
| Remote access        | Mobile app or Safire Control Center-software                   |
| Memory               | Slot MicroSD up to 32GB  |
| Network interface    | Ethernet 10/100 BaseT / RS485 / RTSP / WiFi 802.11b/g/n        |
| Power                | DC 12 V / 1000 mA max. / standard PoE (IEEE802.3af)            |
| Temp. operation      | -10° C ~ +55° C  |
| Dimensions           | 200 (H) x 140 (W) x 15.1 (D) mm                                |
| Weight               | 750 g  |